



**DECLARATION OF PERFORMANCE**

<b>Reference</b>	Cottage-19
<b>Commercial name</b>	Cottage
<b>Product type</b>	Engineered wood flooring – 3-layer 190 x 630-1860 x 14 (3) mm
<b>CE standard</b>	EN14342 : 2013 + A1
<b>Application</b>	Interior floor covering – according to the manufacturer’s specifications and national normative rules – floated installation
<b>Certification number</b>	1393-CPD-0870
<b>System of assessment and verification</b>	System 3
<b>Manufacturer</b>	Lamett Europe Ter Donkt 2 8540 Deerlijk Belgium
<b>Harmonised standard</b>	Timber Research and Development Institute Praha – NB 1393

<b>Essential characteristics</b>	<b>Performance</b>
<b>Reaction of fire</b>	Dfl-s1
<b>Linked with the minimum mean density</b>	650 kg/m <sup>3</sup>
<b>And minimum overall thickness</b>	14 mm
<b>Formaldehyde emission</b>	E1
<b>Pentachlorophenol content</b>	≤ 5 ppm
<b>Slipperiness</b>	-
<b>Thermal conductivity</b>	0.14 W/mK
<b>Biological durability</b>	Class 1

Bruno Descamps  
 CEO Lamett Europe NV